

Claims

1. Method of measuring a down-web coordinate by relating a time-interval, elapsed since a detection of a position-indicating mark applied on a web, to a measured velocity, characterised in that, upon detection of a position-indicating mark, the measured down-web coordinate is synchronised with the indicated down-web coordinate of said mark.
2. Method according to claim 1, wherein, the down-web coordinate is measured in an ascending or a descending mode, depending on a detected roll-orientation information originated from said mark on said web.
3. Method according to claim 2, wherein a selected lane pattern used for registration of the cross web position is reversed automatically, depending on said roll-orientation information, originated from said mark on said web.
4. Method according to any of the preceding claims, wherein a measured down-web starting position of a quality problem area is marked on the web by an ISO-hole.
5. Method for indicating a quality problem area on a web, characterized in that a down-web starting position of the quality problem area is marked on the web by an ISO-hole.
6. System for tracking quality problem areas at continuous-web products, comprising:
  - one or more detection systems for detecting down-web coordinates on a web from a plurality of position-indicating marks applied on said web;
  - one or more product-inspection-systems provided with length-measuring circuitry synchronised with said detected down-web coordinates;
  - a system for data-processing of quality problem areas at least storing the measured down-web coordinates of the respective quality problem areas;

FOE080" 4T42660

sub  
A  
B

- a punch control system for ISO-hole punching provided with length-measuring circuitry synchronised with said detected down-web coordinates.

7. System according to claim 6, wherein the detection systems are suited for detecting a position-indication provided by digitised information contained in said mark.

8. System according to claim 7, wherein the detection systems are suited for detecting information about the roll-orientation provided by digitised information contained in said mark.

9. System for tracking the position of quality problem areas according to  
10 any of the preceding claims 6 -8, wherein said inspection-system makes use of  
a web length-counter that is synchronised by loading the web length-counter  
with the relative down web coordinate information, originated from said mark  
on said web.

10. System according to claim 9, wherein said inspection-system's web  
length-counter is automatically set into an ascending or descending counting  
mode, depending on said roll-orientation information, originated from said  
mark on said web.

11. System according to claim 9 or 10, wherein said inspection-system's web length-counter switches automatically from individual counting-mode into synchronised counting-mode after being triggered via acknowledgement of said mark on said web.

12. System for tracking the position of quality problem areas according to  
any of the preceding claims 6 - 11, wherein said punch control system for ISO-  
hole punching makes use of a web length-counter that is synchronised by  
25 loading the web length-counter with the relative down web position  
information, originated from said mark on said web.

sub  
all

sub  
ab

15 16. Photographic paper according to claim 15, wherein the position-  
B3 indication of a mark is provided by digitised information contained in said  
mark.

17. Photographic paper according to claim 15 or 16, wherein the roll-orientation of a mark is provided by digitised information contained in said mark.

18. Photographic paper according to claim 15 - 17, wherein said marks are not visible for the human eye.

19. Photographic paper according to claim 15 - 18, wherein said marks are applied to the back of the photographic base.

25      20.      Photographic paper according to claim 15 - 19, wherein said marks are  
applied at regular intervals.

21. Photographic paper according to claim 15 - 20, wherein said marks are spaced at a distance ranging from 10 cm to 20 m.

22. Photographic paper according to claim 15 - 21, wherein said marks are applied by pinstamp techniques, moulding.

5 23. Photographic paper according to claim 15 - 21, wherein said marks are applied by laser engraving.

24. Photographic paper according to claim 23, wherein said mark is applied by ink jet printing.

09022414-080301